



HENGZHUN

东莞力显仪器科技有限公司

DONG GUAN LIXIAN INSTRUMENT SCIENTIFIC CO.,LTD

# Introduction

**Name: HZ-7001B Mooney Viscometer**



## **Equipment summary:**

HZ-7001B Mooney Viscometer viscosity for rubber vulcanization index determination. Sample in a certain temperature and pressure, the rotor to a certain degree of rotation torque on the sample to a certain degree of shear stress, measure out the rubber anti-shear torque. Is reclaimed rubber, rubber, wire and cable industry indispensable instrument.

## **Meet the standards:**

Line GB/T1232 "unvulcanized rubber Mooney Viscosity", GB / T 1233 "Rubber, Determination of characteristics of the initial curing Mooney Viscometer" and ISO289, ISO667 and other standards.

## **Applicable industry:**

Applied to rubber, tires, reclaimed rubber factory.

**Tel: +86 769 23388229**

**Fax:+86 769-23388227**

**Website: [www.dglixian.com](http://www.dglixian.com)**

**E-mail: [sales1@hengzhunx.com](mailto:sales1@hengzhunx.com), [sales2@hengzhunx.com](mailto:sales2@hengzhunx.com)**

**Add:Xinhe Management of area, Wanjiang District, Dongguan city, Guangdong province, China**



HENGZHUN

东莞力显仪器科技有限公司

DONG GUAN LIXIAN INSTRUMENT SCIENTIFIC CO.,LTD

**Technical parameter:**

Model	HZ-7001B
Control temperature range	Normal temperature~200℃
Temperature display resolution	0.01℃ (0.1℃ common type of imported temperature controller temperature)
Temperature control accuracy	±0.3℃
Calibration accuracy	Mooney value ±0.5
Rotor speed	2 rotation/ min ±0.02rotation/ min
Torque range	Mooney value 0~200
Torque resolution	Mooney value 0.1
Print content	Date, time, temperature, Mooney scorch curve and MV,T5,T35,T3,T18,@15,@30
Power	50HZ, ~220V±10%

**Tel: +86 769 23388229**

**Fax:+86 769-23388227**

**Website: [www.dglixian.com](http://www.dglixian.com)**

**E-mail: [sales1@hengzhunx.com](mailto:sales1@hengzhunx.com), [sales2@hengzhunx.com](mailto:sales2@hengzhunx.com)**

**Add:Xinhe Management of area, Wanjiang District, Dongguan city, Guangdong province, China**